

THAT WHICH IS CLAIMED IS:

Sub A' →

1. A system for encoding information into a video data stream of a video signal comprising:
a modulation and video synchronization circuit for converting content data into at least one modulated
5 frame of data having video synchronization information;
and
an interleaver operatively connected to said modulation and video synchronization circuit for interleaving the modulated frame of data within at least
10 one selected line of the video data stream.
2. A system according to Claim 1, and further comprising a decode circuit for receiving the video data stream that has been encoded with the content data and extracting the content data therefrom.
3. A system according to Claim 2, wherein said decode circuit further comprises a line deinterleaver for separating video lines having the encoded content data from the video data stream into a modulated frame of
5 content data.
4. A system according to Claim 3, wherein said decode circuit further comprises a DC restoration circuit that restores a DC bias level for any content data in the modulated frame of data.
5. A system according to Claim 3, wherein said decode circuit further comprises a bit and frame

106190" 061901

synchronizer circuit for synchronizing the modulated frame of content data.

6. A system according to Claim 3, wherein said decode circuit further comprises demodulator/decode circuit for demodulating and decoding the modulated frame of content data into the content data.

7. A system according to Claim 1, and further comprising a video signal decoder circuit for receiving a video signal that is compliant with a broadcasting format and converting the video signal into the video data stream to be encoded with content data.

8. A system according to Claim 7, wherein the video signal that is compliant with a broadcasting format comprises one of a National Television System Committee (NTSC), Digital Advanced Television Systems Committee (ATSC), Sequentiel Couleur a Memoire (SECAM), or Phase Alternation Line (PAL) compliant broadcasting format.

9. A system according to Claim 1, and further comprising a video signal formatting circuit operatively connected to said interleaver for receiving the video data stream after interleaving with the modulated frame of content data and formatting the video data stream into a video signal that is compliant with a broadcasting format.

10. A system according to Claim 9, and further comprising a decode circuit for receiving the video signal

that has been encoded with the content data and extracting the content data.

11. A system according to Claim 10, wherein said decode circuit comprises:

a video signal decoder for converting the video signal into a video data stream; and

5 a line separation and restoration circuit that extracts the content data from the video data stream.

12. An encoder for encoding information into a video data stream comprising:

an interleaver for receiving a video data stream and a modulated frame of content data having video

5 synchronization information and interleaving the modulated frame of data within at least one selected video line of the video data stream that is substantially shadowed from viewing on a video display.

13. An encoder according to Claim 12, and further comprising a modulation and video synchronization circuit for converting content data into at least one modulated frame of data having video synchronization

5 information.

14. An encoder according to Claim 12, and further comprising a video signal decoder circuit for receiving a video signal that is compliant with a broadcasting format and converting the video signal into

5 the video data stream to be encoded with content data.

A'
contd

09884897.061901

[illegible]

a video signal decoder for converting the video signal into a video data stream; and

a line separation and restoration circuit that

16. A decoder according to Claim 15, wherein said line separation and restoration circuit further comprises a line deinterleaver for separating video lines having the encoded content data from the video data stream

17. A decoder according to Claim 16, wherein said line separation and restoration circuit further comprises a DC restoration circuit operatively connected to said line deinterleaver and operative on said video data stream for restoring a DC bias level to content data encoded within the modulated frame of data.

18. A decoder according to Claim 16, and further comprising a bit and frame synchronizer circuit for synchronizing the modulated frame of content data.

19. A decoder according to Claim 16, and further comprising a demodulator/decode circuit for

demodulating and decoding the modulated frame of content data into the content data.

20. A method for encoding information into a video signal comprising the step of:

substituting luminance information within the video signal with a modulated frame of content data on one or more lines of the active portion of the video signal to provide an additional information channel on the video signal.

21. A method according to Claim 20, and further comprising the step of forming the modulated frame of data by encapsulating a frame of content data with video synchronization information.

22. A method according to Claim 21, and further comprising the step of embedding a frame sequence and frame marker for synchronization.

23. A method according to Claim 20, and further comprising the step of forming the modulated frame of content data by coding a stream of content data with error correction and modulation information.

24. A method according to Claim 20, and further comprising the step of substituting a modulated frame of content data on one of at least the top or bottom video lines in a video signal, corresponding to the top or bottom of a video display that is substantially shadowed from viewing.

25. A method according to Claim 24, and further comprising the step of formatting the video signal for transmission as one of a National Television System Committee (NTSC), Digital Advanced Television Systems
5 Committee (ATSC), Sequentiel Couleur a Memoire (SECAM), or Phase Alternation Line (PAL) compliant broadcasting format video signal.

26. A method according to Claim 25, and further comprising the step of receiving the video signal after broadcast in a broadcasting format and extracting the
5 content data that had been substituted into the video signal as the additional information channel.

27. A method for encoding information into a video signal of a television signal comprising the step of substituting with a modulated frame of content data one of
5 at least the top or bottom video lines in a video signal corresponding to the top or bottom of a video display that are substantially shadowed from viewing on a television.

28. A method according to Claim 27, wherein the content data comprises digital content data that has been coded with error correction and modulation information for a video signal broadcasting format.

29. A method according to Claim 28, wherein the video signal comprises one of a National Television System Committee (NTSC), Digital Advanced Television Systems
Committee (ATSC), Sequentiel Couleur a Memoire (SECAM), or

Al
cont'd
09884897-061901

- 5 Phase Alternation Line (PAL) compliant broadcasting format.

30. A method according to Claim 28, and further comprising the step of receiving the video signal after broadcast and extracting content data that had been substituted into the video signal as an additional
5 information channel.

31. A method for encoding information into a video signal comprising the steps of:

receiving a video signal as a video data stream to be enhanced with content data;

- 5 converting content data into at least one frame of content data;

adding video synchronization information and modulation data into the at least one frame of content data to form a modulated frame of content data; and

- 10 interleaving the modulated frame of content data within at least one selected video line of the video signal.

32. A method according to Claim 31, and further comprising the step of converting the video data stream that has been interleaved with the modulated frame of content data into a video signal that is compliant with a
5 broadcasting format.

33. A method according to Claim 32, wherein the broadcasting format for the video signal comprises one of a National Television System Committee (NTSC), Digital

A1 cont'd
09084897-061901

Advanced Television Systems Committee (ATSC), Sequentiel
 5 Couleur a Memoire (SECAM), or Phase Alternation Line (PAL)
 compliant broadcasting format.

34. A method according to Claim 31, and further
 comprising the steps of:

broadcasting the video signal;

receiving the broadcasted video signal within a
 5 decoder and converting the received video signal into a
 video data steam; and

extracting the content data from the video data
 stream.

35. A method of processing a video signal
 comprising the steps of:

receiving a video signal as a video data stream
 to be enhanced with content data;

5 converting content data into frames of content
 data;

adding video synchronization information and
 modulation data into the frame of content data to form a
 modulated frame of content data;

10 interleaving the modulated frame of content data
 within at least one selected video line of the video data
 stream;

converting the video data stream into a video
 signal for broadcast;

15 receiving the video signal within a decoder and
 decoding the video signal into a video data stream; and
 extracting the content data from the video data
 stream.

109884897.061904
 A1
 Contd

Al
concl. 5

5

10

10

23